



HyperSpike® AHD Comparison

HyperSpike® HS-18 vs. LRAD 1000Xi™

Critical Specifications	HyperSpike® HS-18	LRAD® 1000Xi™
SPL @ 1 meter, Max	156 dB	153 dB
Distance @ 88 dB	2500 m	1800 m
Frequency Range	245 Hz - 10 kHz	660 Hz - 6.6 kHz
Beam Width	+/- 5°	+/- 15°
Weight	90 lbs (40.8 kg)	87 lbs (39.5 kg)
Surface Area (Wind Loading)	314.2 in ² (0.2 m ²)	1017.9 in ² (0.66 m ²)
STI Measurement (out of 1.0)	0.85	Not Specified
Built in Electronics	Yes	Yes
Dimensions	20" Dia x 18.3" D (50.8 Dia x 46.5 cm D)	36" W x 40" H x 13" D (91.4 cm W x 101.6 cm H x 33 cm D)



Comparison data compiled from HyperSpike® and LRAD® datasheets on 1/31/2013



HS-18



1000Xi™



Ultra Electronics
 USSI
 4868 East Park 30 Drive
 Columbia City
 Indiana, 46725-8869
 USA
 Tel: +1 260.248.3666
 Email: sales@ultra-hyperspike.com
 www.ultra-hyperspike.com
 www.ultra-electronics.com

Follow Us:



Ultra Electronics reserves the right to vary these specifications without notice.
 © Ultra Electronics Inc 2013